


**SERVICE MANUAL**

# **FISHER**

# **RS-270**

**AM/FM STEREO  
QUARTZ LOCKED DIGITAL  
SYNTHESIZER RECEIVER  
(EUROPE)**



**NOTE:**

The photo on the cover shows the unit with a "BRUSHED ALUMINUM" front panel. The "BLACK" version is identical in all respects.

*The first name in high fidelity*

# CONTENTS

Specifications .....	2,3
Functional Block Diagram .....	4
Cabinet & Chassis Exploded View .....	5
Parts List .....	6
Semiconductor Lead Identification .....	7,8
IC Signal Flow .....	9,10,11,12
Power Amplifier Adjustment .....	12,13
Power Level Meter Adjustment .....	13
Harmonic Distortion Test .....	14
AM/FM Tuner Alignment .....	15,16
RF Control P.C.Board Layout .....	17,18
Printed Circuit Board .....	19,20,21,22,23,24
	25,26,27,28,29,30
Parts List .....	31,32,33,34,35,36
Point to Point Wiring Diagram .....	37,38
Schematic Diagram .....	39,40,41,42
Front End Schematic Diagram .....	43

# SPECIFICATIONS


RECEIVER		RS-270
<b>FM SECTION</b>		
Tuning Range		87.5 – 108 MHz
DIN Sensitivity (75 ohms)	Mono	1.8 $\mu$ V
Stereo Trigger Sensitivity		8.0 $\mu$ V
Muting Threshold		8.0 $\mu$ V
S/N Ratio (DIN)	Mono	75 dB
	Stereo	70 dB
Selectivity (DIN)		70 dB
Capture Ratio		0.8 dB
AM Suppression		55 dB
Spurious Rejection		85 dB
IF Rejection		100 dB
Image Rejection		70 dB
Sub-Carrier Suppression (19/38 kHz)		65/70 dB
THD (1 kHz)	Mono	0.3 %
	Stereo	0.4 %
Frequency Response (20 Hz – 15 kHz)		$\pm$ 0.5 dB
Stereo Separation (1 kHz)		50 dB

## SPECIFICATIONS (Continued)

<b>AM SECTION</b>		
Tuning Range		522 – 1602 kHz
Sensitivity		300 $\mu$ V/m
S/N Ratio		55 dB
Image Rejection		50 dB
Selectivity ( $\pm 10$ kHz)		40 dB
THD (30 % Mod.)		0.3 %
Spurious Rejection		55 dB
IF Rejection		45 dB
<b>AMPLIFIER SECTION</b>		
Sine Wave Power	at 1,000 Hz (8 ohms)	2 x 62 W
	20 to 20,000 (8 ohms)	2 x 50 W
Music Power (8 ohms)		2 x 70 W
THD (Rated Output, 8 ohms)		0.02 %
IM (Rated Output, 8 ohms)		0.02 %
Damping Factor (8 ohms)		> 50
Frequency Response (20 Hz – 20 kHz)		$\pm 0.5$ dB
Input Sensitivity and Impedance	Phono MC	60 $\mu$ V/22 ohms
	Phono MM	2.5 mV/50 kohms
	Tape	150 mV/50 kohms
	Aux	150 mV/50 kohms
S/N Ratio (DIN)	Phono	80 dB
	Tape/Aux	100 dB
Treble Control 10 kHz (Turn-over 3 kHz)		$\pm 10$ dB
Bass control 100 Hz (Turn-over 400 Hz)		$\pm 10$ dB
Loudness Control (100 Hz/10 kHz)		+8 dB/+4 dB
<b>GENERAL</b>		
Power Requirements		AC: 110/220 V, 50 Hz
Power Consumption		260 W
Dimensions (W x D x H)		440 x 400 x 132 mm
Weight (approx.)		11.5 kg


Because its products are subject to continuous improvement, Fisher Corporation reserves the right to modify product designs and specifications without notice and without incurring any obligation.

# FUNCTIONAL BLOCK DIAGRAM





# CABINET & CHASSIS EXPLODED VIEW



# PARTS LIST

## PACKING PARTS LIST

Ref. No.	Parts Number	Description
	131 6 1139 85902	Box Corrugate-EXP
	131 6 2119 02121	Bag Polyethylene-EXP
	131 6 3009 31260	Pad, (Right)
	131 6 3009 31270	Pad, (Left)

## ACCESSORIES PARTS LIST

Ref. No.	Parts Number	Description
	131 6 2719 10801	Bag Fan
	131 6 4119 85208	Explanatory Booklet
	131 6 4159 35800	Notes
	131 6 4519 15700	Guarantee Certificate

## CABINET PARTS LIST

Ref. No.	Parts Number	Description
1	131 2 1410 24401	Cover
2	131 2 1410 25000	Cover
3	131 2 1105 26500	Plate Bottom
4	131 2 1801 12900	Leg

## APPEARANCE PARTS LIST

Ref. No.	Parts Number	Description
5	131 0 1008 13200	Plate Dial Assy
6	131 0 1016 36707	Panel Decorate Assy (Silver)
	131 0 1016 36706	Panel Decorate Assy (Black)
6-1	131 0 1001 58203	Push Switch Knob (Silver)
	131 0 1001 58202	Push Switch Knob (Black)
6-2	131 0 1001 58303	Push Switch Knob (Silver)
	131 0 1001 58302	Push Switch Knob (Black)
6-3	131 0 1001 58403	Tuning Switch Knob (Silver)
	131 0 1001 58402	Tuning Switch Knob (Black)
6-4	131 2 1203 49701	Panel Control (Silver)
	131 2 1203 49700	Panel Control (Black)
6-5	131 2 1203 49803	Panel Control (Silver)
	131 2 1203 49802	Panel Control (Black)
6-6	131 2 1205 24800	Decorate Plate Dial
7	131 0 1001 56901	Upper Volume Knob (Silver)
	131 0 1001 56900	Upper Volume Knob (Black)
8	131 0 1001 57001	Under Volume Knob (Silver)
	131 0 1001 57000	Under Volume Knob (Black)
9	131 0 1001 57101	Tone Knob (Silver)
	131 0 1001 57100	Tone Knob (Black)
10	131 2 1601 64100	Knob (Power Switch)
11	131 2 1601 65800	Knob (Push Switch)

## CHASSIS PARTS LIST

Ref. No.	Parts Number	Description
15	131 2 3101 73100	Metal Mount
16	131 2 3101 74300	Metal Mount
17	* 131 2 3301 27300	Chassis
18	* 131 2 3305 29800	Panel Front
19	* 131 2 3306 32102	Panel Rear
20	131 2 3617 18200	Metal Mount Transformer
21	131 2 3701 27800	Mount E Parts
22	131 2 3701 27900	Mount E Parts
23	131 2 4121 00700	Coupling (Push Switch)
24	131 2 4121 00800	Coupling (Power Switch)
25	131 2 4121 00900	Coupling (Push Switch)
26	131 2 6111 14200	Bushing (AC Cord)
27	131 2 6201 28901	Plate Heat Sink (Panel Rear)

## ELECTRICAL PARTS LIST

Ref. No.	Parts Number	Description
30	Δ 4 2312 03680	Switch, Push
31	4 2312 03682	Joint Switch
32	Δ 4 2312 01020	Switch Slide
33	Δ 4 2432 00071	Power Cord
34	Δ 4 2512 13020	Power Transformer
35	4 2579 25260	Bar Antenna AM
36	* 131 0 4001 05731	RF Control P.C.B. Assy
37	* 131 0 4001 05740	Switch P.C.B. Assy
38	* 131 0 4001 05750	Signal P.C.B. Assy
39	* 131 0 4001 05641	Power Amp P.C.B. Assy
40	* 131 0 4001 05652	Power Supply P.C.B. Assy
41	* 131 0 4001 05661	L.E.D. Drive P.C.B. Assy
42	* 131 0 4001 05671	Headphone Jack P.C.B. Assy
43	* 131 0 4001 05681	SP Terminal 1 P.C.B. Assy
44	* 131 0 4001 05691	SP Terminal 2 P.C.B. Assy
45	* 131 0 4001 05700	Phono EQ P.C.B. Assy
46	* 131 0 4001 05710	Tone Amp P.C.B. Assy
47	* 131 0 4001 05720	L.E.D. Lamp P.C.B. Assy
48	* 131 0 4001 06611	Power Ind. P.C.B. Assy
R01,02	R2HCPK185A	Solid 1.8 M 1/2W ±10%


\*—Not a service part.

## PRODUCT SAFETY NOTICE


PRODUCT SAFETY SHOULD BE CONSIDERED WHEN A COMPONENT REPLACEMENT IS MADE IN ANY AREA OF AN UNIT. COMPONENTS INDICATED BY A MARK Δ IN THIS PARTS LIST AND THE SCHEMATIC DIAGRAM SHOW COMPONENTS WHOSE VALUE HAS SPECIAL SIGNIFICANCE TO PRODUCT SAFETY. IT IS PARTICULARLY RECOMMENDED THAT ONLY PARTS SPECIFIED ON THE FOLLOWING PARTS LIST BE USED FOR COMPONENT REPLACEMENT POINTED OUT BY THE MARK.

# SEMICONDUCTOR LEAD IDENTIFICATION


## INTEGRATED CIRCUITS




• TC9137P




• TD6301P




• LA1245




• HA11225  
• HA12016  
• LB1409  
• MSM4053




• LB1416




• STK8250




• HA1457



• TD6104P




• FS-7812M



• TA78L024

# SEMICONDUCTOR LEAD IDENTIFICATION (Continued)


## TRANSISTORS



• 2SK185



• 2SD794



• 2SB560  
• 2SD400  
• 2SD438  
• 2SC2375  
• 2SA1019



• 2SB544  
• 2SC536  
• 2SC930  
• 2SC1000  
• 2SC1570  
• 2SC2274  
• 2SD734



• 2SA978  
• 2SC2385




• 2SK30A




• 2SK104


## DIODES




• DS-135  
• DS-442  
• WZ-240  
• RD4.3E  
• RD5.6E  
• RD7.5E  
• GZA5.6L  
• GZA6.2U  
• GZA20U  
• GZA24L




• DBA-60C



• SVC321



• DS-17  
• DS131



• DS-18

# FM TUNER ALIGNMENT

**FM ALIGNMENT** – FUNCTION switch to FM, MUTING switch to OFF,  
VOLUME control to minimum.

ITEM	GENERATOR	DIAL SETTING	INDICATOR	PROCEDURE
NOTE: The FM IF circuit utilizes a non-turnable ceramic filter which establishes the IF bandpass. To insure symmetrical tuning and selectivity, the IF must be aligned precisely to the center of the filter bandpass, rather than to 10.7 MHz as in conventional LC circuits.				
1. PRELIMINARY DETECTOR ALIGNMENT	Connect 10.7 MHz Sweep Generator to IF and, ground lead to chassis. Adjust for S-curve display. Set generator output to 60 dB.	Position of non-interference	Scope vertical input to Pin 3.	Adjust T01 for maximum gain and best linearity. Adjust T02 for minimum gain and best linearity. See Figure 3.
2. S-CURVE CENTER ALIGNMENT			Connect DC VTVM across Pin 5 and Pin 2.	Adjust VR07 until VTVM reads 0 V. See Figure 4.
3. FINAL DETECTOR ADJUSTMENT (MINIMUM T.H.D.)	Set generator to receiver frequency. Modulate with 400 Hz $\pm 75$ kHz deviation. Connect generator to FM ANT terminals.	Same as above	Harmonic Distortion Analyzer to LEFT REC OUT Jack.	Adjust T02 for minimum distortion.
4. Repeat steps 1 ~ 3 until optimum alignment is reached.				
5. SIGNAL LED ADJUSTMENT	Connect FM RF generator through FM Dummy ANTENNA to FM ANTENNA terminals. Set generator to 98 MHz. (60 dB)	Set to 98 MHz.	Front Panel SIGNAL LED display	Adjust VR06 until the fifth signal LED partly lights up.
NOTE: Confirm that all signal LED light up brightly when the antenna input is increased to 100 dB. Then, set the input in no-signal mode and confirm that all LED are extinguished in all bands. Perform this adjustment after AM Signal LED Adjustment.				
6. FM STOP LEVEL ADJUSTMENT	Set generator to 98 MHz. Adjust ATT output for 5 $\mu$ V. (14 dB)	Same as above	Connect DC VTVM to Pin 8.	Adjust VR01 until VTVM reads 4 V.
7. PLL IC FREE RUN FREQ. CONT. ADJUSTMENT (76 kHz)	Set generator to 98 MHz.	Same as above	Connect frequency counter to Pin 6.	Adjust VR03 in multiplex circuit to obtain 76 kHz $\pm$ 800 Hz on counter.
8. FM STEREO SIGNAL SEPARATION CONTROL	Connect FM stereo SG to FM ANT terminals. 19 kHz signal ON. Main channel, sub channel signal ON. Apply 100 Hz signal from LEFT channel.		Scope and AC-VTVM to RIGHT output jack.	Adjust VR02 for minimum output.
	Same as above for RIGHT channel.		Scope and AC-VTVM to LEFT output jack.	

# RECOMMENDED TEST EQUIPMENTS

The following test equipment is recommended to completely test and align the tuner

- Line Voltage Isolation Transformer
- AC DC Multimeter.
- Accurately Calibrated AC Voltmeter
- Oscilloscope (Flat to 100 kHz Minimum)
- Signal Generator for AM
- IF Gene-scope
- Loop Antenna for AM
- Signal Generator for FM
- Multiplex Generator
- Dummy Antenna for FM

## CONTROL SETTINGS:

Volume Control ..... Maximum (AM-IF and RF, FM-RF); Minimum (FM-IF)  
 Treble Control ..... Center  
 Bass Control ..... Center  
 Balance Control ..... Center  
 Tape Monitor ..... Source  
 Loudness ..... Off

## AM TUNER ALIGNMENT

**AM ALIGNMENT** – FUNCTION switch to AM position

Maintain generator output as low as possible for suitable indication.

ITEM	GENERATOR	AM DIAL SETTING	INDICATOR	PROCEDURE
1. IF ALIGNMENT	Connect 450 kHz sweep generator to TP1 and ground lead to chassis. Use 0.1 $\mu$ F capacitor in series with generator lead.	Position of non-interference Minimum Frequency	Scope vertical input to Pin 7 and ground lead to chassis. Set vertical sensitivity to 0.2 V/cm.	Adjust T03, T04 for maximum gain and best symmetry. Keep signal low enough for noise on response as shown in Figure 1.
2. FRONT END ALIGNMENT (603 kHz)	AM generator to EXT AM ANT and GND terminals Set to 603 kHz. Modulate with 400 Hz (30 % modulation).	Set to 600 kHz.	Connect oscilloscope to Record Out terminal.	Adjust Bar Antenna to maximum output. See Figure 2.
3. FRONT END ALIGNMENT (1404 kHz)	Set to 1404 kHz.	Set to 1400 kHz	Same as above	Adjust TC02 to maximum output.
4. TRACKING ALIGNMENT (522 kHz)		Set to 522 kHz	Connect DC VTVM to Pin 9.	Adjust T05 until VTVM reads 1.2 V.
5. TRACKING ALIGNMENT (1602 kHz)		Set to 1602 kHz	Same as above	Adjust TC01 until VTVM reads 8.0 V.
6. AM STOP ADJUSTMENT	Same as above Set generator at 999 kHz to antenna input (64 dB).	Set to 999 kHz		Check that Auto Stop Function works at 999 kHz on DIGITAL Counter.
7. SIGNAL IND. ADJUSTMENT	Set generator at 1000 kHz to antenna input (100 dB).	Same as above		Adjust VR05 until all LEDs light up.

## RECOMMENDED TEST EQUIPMENTS

The following test equipments are recommended to completely test and align the Amplifier:

- Line Voltage Isolation Transformer
- AC DC Multimeter.
- Accurately Calibrated AC Voltmeter.
- Oscilloscope (Flat to 100 kHz Minimum)
- Low-Distortion Audio Sine-Wave Generator
- Harmonic Distortion Analyzer
- Two (2) Load Resistors 8-ohms, 250 Watts (Minimum Rating)

## HARMONIC DISTORTION TEST

**CAUTION:** Limit the following tests to no more than ten minutes each. Use 8-ohm resistors, with a minimum power rating of 250 watts when connecting a load across the SPEAKERS terminal.

### CONTROL SETTINGS:

Unplug the AC power cord and set the front panel controls as follows:

- BASS, TREBLE, and BALANCE controls to center positions.
- POWER switch to OFF
- SPEAKERS switch to OFF
- FUNCTION switch to AUX
- MODE switch to STEREO
- TAPE MONITOR switch to SOURCE
- LOUDNESS switch to OFF
- VOLUME control to MINIMUM position
- LEFT CHANNEL DRIVEN

### ONE CHANNEL DRIVEN:


- 1) Connect a low distortion audio generator to LEFT AUX IN jack. Set generator frequency to 1 kHz and output to minimum.
- 2) Connect an 8-ohm load resistor between SPEAKERS A LEFT and COM terminals. Connect a Harmonic Distortion Analyzer and an AC VTVM in parallel across the 8-ohm load.
- 3) Connect the AC power cord and set SPEAKERS switch to A. Turn VOLUME control to MAX.
- 4) Increase generator output for 50 Watts RMS (20 V across the 8-ohm load). Harmonic Distortion Analyzer should measure 0.02 % distortion or less.
- 5) Repeat steps 1 through 4 for RIGHT CHANNEL.

### BOTH CHANNELS DRIVEN

Connect 8-ohm load resistors across LEFT and RIGHT MAIN SPEAKERS terminals. Set MODE switch to "MONO". Adjust generator output and "BALANCE" control for 50 Watts at Left and Right Channels (20 volts across the 8-ohm loads). Harmonic Distortion Analyzer should measure 0.02 % distortion or less at each channel.

**CAUTION:** This precision high-fidelity instrument should be serviced only by qualified personnel, trained in the repair of transistor equipment and printed circuitry.

## POWER AMP P.C.BOARD (TOP VIEW)



## POWER LEVEL METER ADJUSTMENT


### BEFORE ADJUSTMENT

1. Connect Audio Frequency Generator to the AUX input terminal.
2. Set Function Switch to "AUX" position.
3. Connect dummy load resistors (8 ohms) to the speaker terminal.
4. Use a DC V.T.V.M. (input impedance: more than 50 kohms/V).

### POWER LEVEL METER ADJUSTMENT

1. Adjust Volume of the unit or Attenuator of the oscillator until AC V.T.V.M. reads 11.0 V. At this time, adjust VR01 and VR02 until the eighth LED lights up (The output becomes 50 W).
2. Reduce the input and set the indication of AC V.T.V.M. to 300 mV. Then, adjust VR03 and VR04 until the first LED lights up. (Confirm Items 1 and 2 again).

## L.E.D. DRIVE P.C.BOARD (TOP VIEW)



# CHANNEL SPACE CHANGE-OVER IN SYNTHESIZER TUNER

Frequency spaces in FM/AM Synthesizer Tuner are made at every 50 kHz (FM) and 9 kHz (AM) point. The above frequency spaces can be changed over to 100 kHz (FM) and 10 kHz (AM) points when used in U.S.A. Change the spaces by the following procedures.

1. Turn off the power switch.
2. Remove R157 (100 k-ohm). (Fig. 1).
3. Connect Pin No. 6 of IC01 (TC9137P) to GND with a jumper lead. (Fig. 2).




Figure 1




Figure 2

## POWER AMPLIFIER ADJUSTMENT

### BEFORE ADJUSTMENT

1. After setting the power switch to the ON position, allow a few minutes before making adjustment, to be sure of the most stable operation.
2. Connect dummy load resistors (8 ohms) to the Speaker terminals.
3. Use a DC V.T.V.M. (input impedance: More than 50 kohms/V).

### IDLING CURRENT ADJUSTMENT

1. Left channel
  - Connect DC V.T.V.M. between TP1 and TP2.
  - Adjust VR03 to 40mV DC voltmeter indication.


### ZERO BALANCE ADJUSTMENT

- Connect DC V.T.V.M. to the speaker output terminal and turn the volume control fully to the minimum position. Turn VR01 and VR02 in P.C.B. under the above condition until the output voltage becomes  $0 \pm 50$  mV.


2. Right channel
  - Connect DC V.T.V.M. between TP3 and TP4.
  - Adjust VR04 to 40mV DC voltmeter indication.




## PRE SCALAR IC TD6104P SIGNAL FLOW




## L.E.D. LEVEL METER IC LB1416 SIGNAL FLOW




## L.E.D. LEVEL METER IC LB1409 SIGNAL FLOW




## PLL CONTROL IC TC9137P SIGNAL FLOW




## STATIC DRIVER IC TD6301P SIGNAL FLOW



## FM IF IC HA11225 SIGNAL FLOW




## FM MPX IC HA12016 SIGNAL FLOW




# RF CONTROL P.C.BOARD LAYOUT

WITH OSCILLOSCOPE TIME BASE SETTINGS  
(TOP VIEW)



# RF CONTROL P.C.BOARD (BOTTOM VIEW)




RF CONTROL P.C.B. IC PIN NUMBERS VOLTAGES																					
SYMBOL No.	DEVICE	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20
IC01	HA11225	2.0V	2.0V	2.0V	0V	0V	5.4V	5.6V	5.7V	5.7V	5.7V	13.6V	3.4V	0V	0V	4.8V	3.6V	—	—	—	—
IC02	HA12016	13.2V	3.8V	5.5V	6.6V	11.4V	11.4V	6.7V	0V	4.8V	2.5V	2.5V	11.3V	2.5V	2.5V	2.5V	0V	—	—	—	—
IC04	LA1245	5.7V	2.2V	2.8V	0V	11.0V	2.1V	11.8V	11.8V	2.9V	8.7V	0.7V	0V	2.2V	12.8V	1.7V	0V	2.2V	5.7V	5.7V	3.0V



# TONE AMP P.C.BOARD


## (BOTTOM VIEW)




TONE AMP P.C.B. IC PIN NUMBERS VOLTAGES									
SYMBOL No.	DEVICE	1	2	3	4	5	6	7	8
IC01,02	HA1457	-0.2V	-	-0.3V	-22V	-21V	-0.2V	-0.3V	23.2V

RF CONTROL P.C.B. TRANSISTOR DC VOLTAGES														
SYMBOL No.	DEVICE	B	C	E	SYMBOL No.	DEVICE	B	C	E	SYMBOL No.	DEVICE	B	C	E
Q01	2SC930	3.1V	11.8V	2.4V	Q07	2SC536	0V	2.2V	2.2V	Q10	2SC1000	0.7V	14.3V	0V
Q02	2SC536	1.5V	5.6V	5.7V	Q08	2SC536	1.8V	9.5V	1.2V	Q12	2SC1000	0.6V	26.4V	0V
Q03	2SC536	0.7V	0V	0V			G	D	S	Q13	2SD734	0.7V	0V	0V
Q04	2SC536	0V	4.0V	0V	Q09	2SK30A	0.9V	3.5V	0.7V	Q14	2SD734	0.6V	0V	0V
Q05	2SC536	0V	11.3V	0V	Q11	2SK30A	0.2V	3.5V	0.6V					


## SP TERMINAL 1 P.C.BOARD (BOTTOM VIEW)



## SP TERMINAL 2 P.C.BOARD (BOTTOM VIEW)




## SIGNAL P.C.BOARD (BOTTOM VIEW)







# L.E.D. LAMP P.C.BOARD (BOTTOM VIEW)



# L.E.D. DRIVE P.C.BOARD (BOTTOM VIEW)




# PHONO EQ P.C.BOARD (BOTTOM VIEW)



IC PIN NUMBERS VOLTAGES									
SYMBOL No.	DEVICE	1	2	3	4	5	6	7	8
IC01,02	HA1457	0V	-	0V	-22V	-21V	0V	0V	23.2V


TRANSISTOR DC VOLTAGES									
SYMBOL No.	DEVICE	B	C	E	SYMBOL No.	DEVICE	B	C	E
Q01,02	2SC2385	0.6V	1.9V	0V	Q06	2SB544	-7.5V	-17V	-6.8V
Q03,04	2SA978	-0.6V	-1.9V	0V			G	D	S
Q05	2SD400	7.5V	17.1V	6.8V	Q07	2SK104	7.5V	17.1V	7.5V
					Q08	2SK104	-17V	-7.5V	-17V

# HEADPHONE P.C.BOARD (BOTTOM VIEW)





# POWER AMP P.C.BOARD (BOTTOM VIEW)



IC PIN NUMBERS VOLTAGES											
SYMBOL No.	DEVICE	1	2	3	4	5	6	7	8	9	10
IC01,02	STK8250	-1.2V	-47V	-0.6V	-0.7V	0V	0V	0.7V	0.7V	48V	1.2V


TRANSISTOR DC VOLTAGES									
SYMBOL No.	DEVICE	G	D	S	SYMBOL No.	DEVICE	B	C	E
Q01,02	2SK185	0V	9.3V	0.3V	Q15,16	2SC2375	-45V	-1.8V	-45V
		B	C	E	Q17,18	2SD438	0.2V	1.0V	0V
Q03,04,05,06	2SC1570	9.9V	35.0V	9.3V	Q19,20	2SB560	-0.2V	-1.0V	0V
Q07,08,09,10	2SC1570	35.0V	44.1V	34.3V	Q21	2SC536	0V	5.5V	0V
Q11,12	2SA1019	44.1V	-29.7V	44.8V	Q22	2SC536	2.0V	1.5V	1.4V
Q13,14	2SA1019	43.8V	1.9V	44.5V	Q23	2SC2274	1.4V	1.5V	0.8V

# POWER SUPPLY P.C.BOARD (BOTTOM VIEW)



TRANSISTOR DC VOLTAGES

SYMBOL No.	DEVICE	B	C	E
Q01	2SD438	43V	43.2V	42.4V
Q02	2SD438	21.6V	36.8V	21.1V
Q03	2SD438	25.4V	37.7V	24.8V
Q04	2SB560	-24.3V	-36.9V	-23.7V
Q05	2SC536	13.3V	13.4V	12.6V
Q06	2SD794	6.5V	12.6V	5.9V

# POWER IND. P.C.BOARD (BOTTOM VIEW)



# SWITCH P.C.BOARD (BOTTOM VIEW)



## PARTS LIST

RF CONTROL P.C.B. Assy  
131 0 4001 05731

Ref. No.	Parts Number	Description	Ref. No.	Parts Number	Description
	4 1252 00250	Tuner Pack (Component parts used in Front End are not serviceable and available.)	C38,39	C1HRY-475APA	Electrolytic 4.7 μF 50V
	4 2142 00060	Digitron	C40	C1CCZN223YPA	Ceramic 0.022 μF 16V ±30%
	4 2212 00150	Resistor 20kx11 ±10%	C41	C1HCZK102BPA	Ceramic 1000 pF 50V ±10%
	4 2252 00080	7.2 MHz Crystal	C42	C1HYYZ473APA	Ceramic 0.047 μF 50V +80,—20%
TC01,02	4 2249 20440	Trimmer Cap	C43,44	C1HYYZ223APA	Ceramic 0.022 μF 50V +80,—20%
T01	4 2562 00291	FM IFT	45		
T02	4 2562 00301	FM IFT	C46	C1HCYK470APA	Ceramic 47 pF 50V ±10%
T03	4 2562 00320	AM IFT	C47	C1CCZN223YPA	Ceramic 0.022 μF 16V ±30%
T04	4 2562 00330	AM IFT	C49	C1HSEJ411A	Styrol 410 pF 50V ±5%
T05	4 2582 00300	AM OSC Coil	C50	C1HYYZ473APA	Ceramic 0.047 μF 50V +80,—20%
	4 2372 00860	Antenna Terminal 3P	C52	C1HRY-475APA	Electrolytic 4.7 μF 50V
	4 2522 00110	AF Filter	C53	C1HYYZ473APA	Ceramic 0.047 μF 50V +80,—20%
	4 2599 20300	Balun	C54	C1HRY-474APA	Electrolytic 0.47 μF 50V
L01	4 2532 00200	Choke Coil 8.2 mH	C55	C1HFYK103APA	Mylar 0.01 μF 50V ±10%
L03	4 2532 00012	Choke Coil 2.2 μH	C56	C1CRE-107A	Electrolytic 100 μF 16V
L05	4 2532 00210	Choke Coil 33 μH	C57	C1HYYZ102APA	Ceramic 0.001 μF 50V +80,—20%
CF01,02	4 2272 00261	Ceramic Filter	C58	C1HRY-475APA	Electrolytic 4.7 μF 50V
03			C59	C1HFYK183APA	Mylar 0.018 μF 50V ±10%
CF04	4 2272 00250	Ceramic Filter	C60	C1HFYK563APA	Mylar 0.056 μF 50V ±10%
CF05	4 2272 00240	Ceramic Filter	C61	C1HFYK222APA	Mylar 0.0022 μF 50V ±10%
VR01	4 2222 01400	VR 10k-B	C62	C1HRY-105APA	Electrolytic 1 μF 50V
VR02	4 2222 01010	VR 50k-B	C63	C1HFYK103APA	Mylar 0.01 μF 50V ±10%
VR03	4 2222 01000	VR 5k-B	C64	C0JRE-337A	Electrolytic 330 μF 6.3V
VR05	4 2222 01040	VR 20k-B	C65	C1HRY-224LPA	Electrolytic 0.22 μF 50V
VR06	4 2222 01010	VR 50k-B	C68,69	C1ERY-106APA	Electrolytic 10 μF 25V
VR07	4 2222 01020	VR 200k-B	C70,71	C1HRY-475APA	Electrolytic 4.7 μF 50V
			C72	C1HYYZ473APA	Ceramic 0.047 μF 50V +80,—20%
			C73	C1HYYZ103APA	Ceramic 0.01 μF 50V +80,—20%
			C74	C1HYYZ473APA	Ceramic 0.047 μF 50V +80,—20%
			C75,76	C1HCDJ270CH	Ceramic 27 pF 50V ±5%
			C77	C1HRY-105LPA	Electrolytic 1 μF 50V
			C78	C0JRE-337A	Electrolytic 330 μF 6.3V
			C79	4 2232 00510	Electrolytic 10000 μF 6.3V
C01	C1HYYZ223APA	Ceramic 0.022 μF 50V +80,—20%	C80	C1HYYZ473APA	Ceramic 0.047 μF 50V +80,—20%
C02,03	C1CCZN223YPA	Ceramic 0.022 μF 16V ±30%	C81	C1HCYK330APA	Ceramic 33 pF 50V ±10%
C05	C1HRY-104LPA	Electrolytic 0.1 μF 50V	C82	C1HFYK473APA	Mylar 0.047 μF 50V ±10%
C06	C1CCZN223YPA	Ceramic 0.022 μF 16V ±30%	C90	C1CCZN223YPA	Ceramic 0.022 μF 16V ±30%
C07	C1HYYZ473APA	Ceramic 0.047 μF 50V +80,—20%			
C08	C1HYDK331R	Ceramic 330 pF 50V ±10%			
C09	C1HRY-474APA	Electrolytic 0.47 μF 50V			
C10	C1HYYZ473APA	Ceramic 0.047 μF 50V +80,—20%			
C11	C1CRY-476APA	Electrolytic 47 μF 16V			
C12	C1HYYZ473APA	Ceramic 0.047 μF 50V +80,—20%			
C13	C1HYDK122R	Ceramic 0.0012 μF 50V ±10%			
C14	C1HRY-474APA	Electrolytic 0.47 μF 50V			
C15,16	C1HYYZ473APA	Ceramic 0.047 μF 50V +80,—20%			
C17	C1CRY-107APA	Electrolytic 100 μF 16V			
C18	C1HYYZ473APA	Ceramic 0.047 μF 50V +80,—20%			
C19	C1HRY-104LPA	Electrolytic 0.1 μF 50V			
C20	C1CRY-476APA	Electrolytic 47 μF 16V			
C21	C1CRE-107A	Electrolytic 100 μF 16V			
C22,23	C1CRY-336APA	Electrolytic 33 μF 16V			
C24,25	C1HFYK102APA	Mylar 0.001 μF 50V ±10%			
C26,27	C1HRY-225LPA	Electrolytic 2.2 μF 50V			
C28	C1HRY-105LPA	Electrolytic 1 μF 50V			
C29	C1HFYK473APA	Mylar 0.047 μF 50V ±10%			
C30	C1ERY-335LPA	Electrolytic 3.3 μF 25V			
C31	C1HFYK102APA	Mylar 0.001 μF 50V ±10%			
C32	C1HRY-105APA	Electrolytic 1 μF 50V			
C33	C1ERY-335LPA	Electrolytic 3.3 μF 25V			
C35,36	C1HRY-475APA	Electrolytic 4.7 μF 50V			
C37	C1CRY-106APA	Electrolytic 10 μF 16V			
			D01,02	205 5 9040 44210	Diode, DS-442
			03,04		
			05,06		
			07,08		
			09,10		
			D11	202 5 1220 32113	Variable Capacitor Diode, SVC321C-2
			D12	205 5 9040 44210	Diode, DS-442
			D13	DNN-RD5R6EB2	Diode, RD5.6EB2
			D14,16	205 5 9040 44210	Diode, DS-442
			17,18,19,20		
			21,22,23,25		
			26,27,28,29		
			D30	202 5 1220 32113	Variable Capacitor Diode, SVC321C-2
			D40	205 5 9040 44210	Diode, DS-442
			IC01	IKK-HA11225	IC, HA11225
			IC02	IKK-HA12016	IC, HA12016
			IC03	206 5 2341 41610	IC, LB1416
			IC04	206 5 0191 24510	IC, LA1245
			IC05	IPP-MSM4053RS	IC, MSM4053RS

# PARTS LIST (Continued)

Ref. No. Parts Number Description

## SEMICONDUCTORS

IC06	ITT-TD-6104P	IC, TD6104P
IC07	ITT-TC9137P	IC, TC9137P
IC08	ITT-TD6301P	IC, TD6301P
Q01	203 5 5500 93050	TR 2SC930 E, F
Q02,03	203 5 5000 53650	TR 2SC536 E, F
04,05		
07,08		
Q09	TTT-2SK30A-O	TR 2SK30A O
Q10	TTT-2SC1000GBL	TR 2SC1000G BL
Q13	203 5 4570 73452	TR 2SD734 E, F
Q16,51	203 5 5000 53650	TR 2SC536 E, F
52		

## RESISTORS

R01	R2EDZJ224APA	Carbon	220k	1/4W	±5%
R02	R2EDZJ104APA	Carbon	100k	1/4W	±5%
R03	R2EDZJ152APA	Carbon	1.5k	1/4W	±5%
R04	R2EDZJ471APA	Carbon	470	1/4W	±5%
R05	R2EDZJ391APA	Carbon	390	1/4W	±5%
R06	R2EDZJ102APA	Carbon	1k	1/4W	±5%
R07	R2EDZJ333APA	Carbon	33k	1/4W	±5%
R08	R2EDZJ331APA	Carbon	330	1/4W	±5%
R09	R2EDZJ103APA	Carbon	10k	1/4W	±5%
R10	R2EDZJ471APA	Carbon	470	1/4W	±5%
R11	R2EDZJ123APA	Carbon	12k	1/4W	±5%
R12	R2EDZJ823APA	Carbon	82k	1/4W	±5%
R13	R2EDZJ104APA	Carbon	100k	1/4W	±5%
R14	R2EDZJ392APA	Carbon	3.9k	1/4W	±5%
R15	R2EDZJ103APA	Carbon	10k	1/4W	±5%
R16,17	R2EDZJ473APA	Carbon	47k	1/4W	±5%
18					
R19	R2EDZJ332APA	Carbon	3.3k	1/4W	±5%
R20	R2EDZJ682APA	Carbon	6.8k	1/4W	±5%
R21	R2EDZJ473APA	Carbon	47k	1/4W	±5%
R22	R2EDZJ124APA	Carbon	120k	1/4W	±5%
R23	R2EDZJ104APA	Carbon	100k	1/4W	±5%
R24	R2EDZJ124APA	Carbon	120k	1/4W	±5%
R25	R2EDZJ563APA	Carbon	56k	1/4W	±5%
R26	R2EDZJ222APA	Carbon	2.2k	1/4W	±5%
R27	R2EDPJ220A	Carbon	22	1/4W	±5%
R28	R2EDZJ222APA	Carbon	2.2k	1/4W	±5%
R29,30	R2EDZJ183APA	Carbon	18k	1/4W	±5%
R31	R2EDZJ222APA	Carbon	2.2k	1/4W	±5%
R32,33	R2EDZJ473APA	Carbon	47k	1/4W	±5%
R34,35	R2EDZJ332APA	Carbon	3.3k	1/4W	±5%
R36,37	R2EDZJ562APA	Carbon	5.6k	1/4W	±5%
R38	R2EDZJ102APA	Carbon	1k	1/4W	±5%
R39	R2EDZJ562APA	Carbon	5.6k	1/4W	±5%
R40	R2EDZJ104APA	Carbon	100k	1/4W	±5%
R41,42	R2EDZJ473APA	Carbon	47k	1/4W	±5%
R43	R2EDZJ104APA	Carbon	100k	1/4W	±5%
R44	R2EDZJ561APA	Carbon	560	1/4W	±5%
R45,46	R2EDZJ103APA	Carbon	10k	1/4W	±5%
R48	R2EDZJ102APA	Carbon	1k	1/4W	±5%
R49	R2EDZJ683APA	Carbon	68k	1/4W	±5%
R50	R2EDZJ103APA	Carbon	10k	1/4W	±5%
R51	R2EDZJ154APA	Carbon	150k	1/4W	±5%
R52	R2EDZJ153APA	Carbon	15k	1/4W	±5%

Ref. No. Parts Number Description

## RESISTORS

R53	R2EDPJ101A	Carbon	100	1/4W	±5%
R54	R2EDZJ221APA	Carbon	220	1/4W	±5%
R55	R2EDZJ152APA	Carbon	1.5k	1/4W	±5%
R56	R2EDZJ222APA	Carbon	2.2k	1/4W	±5%
R57	R2EDZJ104APA	Carbon	100k	1/4W	±5%
R58	R2EDZJ680APA	Carbon	68	1/4W	±5%
R59	R2EDZJ102APA	Carbon	1k	1/4W	±5%
R60	R2EDZJ182APA	Carbon	1.8k	1/4W	±5%
R61	R2EDZJ224APA	Carbon	220k	1/4W	±5%
R62,63	R2EDZJ103APA	Carbon	10k	1/4W	±5%
R64	R2EDZJ392APA	Carbon	3.9k	1/4W	±5%
R65	R2EDZJ473APA	Carbon	47k	1/4W	±5%
R66	R2EDZJ152APA	Carbon	1.5k	1/4W	±5%
R67	R2EDPJ470A	Carbon	47	1/4W	±5%
R68	R2EDZJ332APA	Carbon	3.3k	1/4W	±5%
R69	R2EDZJ334APA	Carbon	330k	1/4W	±5%
R70	R2EDZJ104APA	Carbon	100k	1/4W	±5%
R71	R2EDZJ332APA	Carbon	3.3k	1/4W	±5%
R72	R2EDZJ122APA	Carbon	1.2k	1/4W	±5%
R73	R2EDZJ124APA	Carbon	120k	1/4W	±5%
R74,75	R2EDZJ272APA	Carbon	2.7k	1/4W	±5%
R76	R2EDZJ471APA	Carbon	470	1/4W	±5%
R77	R2EDZJ103APA	Carbon	10k	1/4W	±5%
R78,79	R2EDZJ562APA	Carbon	5.6k	1/4W	±5%
R80,81	R2EDZJ393APA	Carbon	39k	1/4W	±5%
R89	R2EDZJ681APA	Carbon	680	1/4W	±5%
R91	R2EDZJ471APA	Carbon	470	1/4W	±5%
R92	R2EDZJ224APA	Carbon	220k	1/4W	±5%
R93	R2EDZJ104APA	Carbon	100k	1/4W	±5%
R94	R2EDZJ471APA	Carbon	470	1/4W	±5%
R95	R2EDZJ104APA	Carbon	100k	1/4W	±5%
R96	R2EDZJ334APA	Carbon	330k	1/4W	±5%
R97,98	R2EDZJ224APA	Carbon	220k	1/4W	±5%
R99	R2EDZJ103APA	Carbon	10k	1/4W	±5%
R100	R2EDZJ333APA	Carbon	33k	1/4W	±5%
R102,103	R2EDZJ104APA	Carbon	100k	1/4W	±5%
104,105					
R106	R2EDZJ103APA	Carbon	10k	1/4W	±5%
R107	R2EDZJ471APA	Carbon	470	1/4W	±5%
R108	R2EDZJ683APA	Carbon	68k	1/4W	±5%
R109,110	R2EDZJ473APA	Carbon	47k	1/4W	±5%
R111	R2EDZJ103APA	Carbon	10k	1/4W	±5%
R112	R2EDZJ471APA	Carbon	470	1/4W	±5%
R113,114	R2EDZJ332APA	Carbon	3.3k	1/4W	±5%
R115	R2EDPJ101A	Carbon	100	1/4W	±5%
R116	R2HXB222A	Oxide Metal Film	2.2k	1/2W	±5%
R117	R2EDZJ104APA	Carbon	100k	1/4W	±5%
R150	R2EDZJ154APA	Carbon	150k	1/4W	±5%
R151	R2EDZJ473APA	Carbon	47k	1/4W	±5%
R152	R2EDZJ104APA	Carbon	100k	1/4W	±5%
R153	R2EDZJ682APA	Carbon	6.8k	1/4W	±5%
R154	R2EDZJ103APA	Carbon	10k	1/4W	±5%
R155	R2EDZJ472APA	Carbon	4.7k	1/4W	±5%
R156	R2EDZJ103APA	Carbon	10k	1/4W	±5%
R157	R2EDZJ104APA	Carbon	100k	1/4W	±5%

## PARTS LIST (Continued)

### SWITCH P.C.B. Assy 131 0 4001 05740

Ref. No.	Parts Number	Description
	4 2312 01880	Key Board Switch
	4 2312 04620	Switch Push 1Key
	131 2 6113 39400	Shelter

#### SEMICONDUCTORS

D01,02 03,04 05,06	DYY-SLR-54GG	Diode, SLR-54GG (LED)
D07 D08	DYY-SLR-54UR 205 5 9040 44210	Diode, SLR-54UR (LED) Diode, DS-442

#### RESISTORS

R01	R2EDPJ181A	Carbon	180	1/4W	±5%
R02	R2EDPJ331A	Carbon	330	1/4W	±5%

### SIGNAL P.C.B. Assy 131 0 4001 05750

Ref. No.	Parts Number	Description
----------	--------------	-------------

#### SEMICONDUCTORS

D01,02 03,04 05	DYY-SLR-54GG	Diode, SLR-54GG (LED)
D06	DYY-SLR-54UR	Diode, SLR-54UR (LED)

### POWER AMP P.C.B. Assy 131 0 4001 05641

Ref. No.	Parts Number	Description
----------	--------------	-------------

VR01,02	4 2222 00240	VR 100-B
VR03,04	4 2229 25100	VR 47k-B
	4 2322 00090	Relay
△	4 2349 21570	Fuse T 6.3 A
L01,02	4 2532 00180	RF Filter
	HLL-PTH487A-BF	Posistor

#### CAPACITORS

C01,02	C1HCYK271APA	Ceramic	270 pF	50V	±10%
C03	C1ERE-476A	Electrolytic	47 μF	25V	
C04	C1ERY-476APA	Electrolytic	47 μF	25V	
C05,06	C1HCYK221APA	Ceramic	220 pF	50V	±10%
C07,08 09,10	C1HCDJ120SL	Ceramic	12 pF	50V	±5%
C11,12	C1HCDD080SL	Ceramic	8 pF	50V	±0.5%
C13,14 15,16	C1JRE-337A	Electrolytic	330 μF	63V	
C17,18	C1HCDJ120SL	Ceramic	12 pF	50V	±5%
C19,20	C1HCDK331SL	Ceramic	330 pF	50V	±10%
C21	C1HCYK331APA	Ceramic	330 pF	50V	±10%
C22	C1HCDK331SL	Ceramic	330 pF	50V	±10%
C23,24	C1HFKYK123APA	Mylar	0.012 μF	50V	±10%
C25,26	C1HFRK104A	Mylar	0.1 μF	50V	±10%
C27,28	C1HFKYK153APA	Mylar	0.015 μF	50V	±10%
C29	C1HFRK153A	Mylar	0.015 μF	50V	±10%
C30	C1HFKYK153APA	Mylar	0.015 μF	50V	±10%
C31,32	C1EAEN107A	Electrolytic	100 μF	25V	±30%

Ref. No.	Parts Number	Description
----------	--------------	-------------

#### CAPACITORS

C33	C1ERE-226A	Electrolytic	22 μF	25V	
C34,35	4 2232 00580	Electrolytic	8200 μF	63V	
C36,37 38,39	C2HYDP103A	Ceramic	0.01 μF	500V	+100,-0%
C40,41	C1HFKYK102APA	Mylar	0.001 μF	50V	±10%
C42,43 44,45	C1HCDK101A	Ceramic	100 pF	50V	±10%

#### SEMICONDUCTORS

D01,02	202 5 3210 24010	Diode, GZA 24L
D03,04 05,06 07,08 09,10 11,12 13,14 15,16	205 5 9040 44210	Diode, DS-442
D17,18	202 5 3210 05610	Diode, GZA 5.6L
D19,20 21	205 5 9040 44210	Diode, DS-442
D22	202 5 2470 13540	Diode, DS-135
D23	202 5 2750 06015	Diode, DBA-60C-K15
IC01,02	206 5 4368 25010	IC, STK8250
Q01,02	TVV-2SK185	TR 2SK185 (Dual)
Q03,04 05,06 07,08 09,10	203 5 5251 57070	TR 2SC1570 G, H
Q11,12	203 5 6731 01960	TR 2SA1019 F, G
Q15,16	203 5 6722 37560	TR 2SC2375 F, G
Q17,18	203 5 6830 43850	TR 2SD438 E, F
Q19,20	203 5 6840 56050	TR 2SB560 E, F
Q21,22	203 5 5000 53660	TR 2SC536 F, G
Q23	203 5 7252 27450	TR 2SC2274 E, F

#### RESISTORS

R01,02	R2EDZJ104APA	Carbon	100k	1/4W	±5%
R03,04	R2EDZJ823APA	Carbon	82k	1/4W	±5%
R05,06	R2EDZJ223APA	Carbon	22k	1/4W	±5%
R07,08	R2EDZJ682APA	Carbon	6.8k	1/4W	±5%
R09,10	R2HZBJ182A	Oxide Metal Film	1.8k	1/2W	±5%
R11,12 13,14	R2HZPK470A	Fuse	47	1/2W	±10%
R15,16 17,18	R2EDZJ470APA	Carbon	47	1/4W	±5%
R19,20 21,22	R2EDZJ822APA	Carbon	8.2k	1/4W	±5%
R23,24	R2EDZJ681APA	Carbon	680	1/4W	±5%
R25,26	R2EDZJ123APA	Carbon	12k	1/4W	±5%
R27,28	R2EDZJ102APA	Carbon	1k	1/4W	±5%
R29,30	R2EEZJ223APA	Carbon	22k	1/4W	±5%
R31,32 33,34	R2EDZJ222APA	Carbon	2.2k	1/4W	±5%
R35,36 37,38	R2EDZJ101APA	Carbon	100	1/4W	±5%
R39,40 41,42	R2EDZJ471APA	Carbon	470	1/4W	±5%



## PARTS LIST (Continued)

Ref. No.	Parts Number	Description
<b>CAPACITORS</b>		
R43,44	R2EDZJ272APA	Carbon 2.7k 1/4W ±5%
R45,46	R2EDZJ121APA	Carbon 120 1/4W ±5%
47,48		
R49,50	R2EDZJ101APA	Carbon 100 1/4W ±5%
51,52		
R53,54	R2EDZJ103APA	Carbon 10k 1/4W ±5%
R55,56	R2EDZJ102APA	Carbon 1k 1/4W ±5%
57,58		
R59,60	R2EDZJ563APA	Carbon 56k 1/4W ±5%
61,62		
R63,64	R2EDZJ331APA	Carbon 330 1/4W ±5%
65,66		
R67,68	R2EDZJ223APA	Carbon 22k 1/4W ±5%
R69,70	4 2212 00050	Cement 0.47 5Wx2 ±10%
R71,72	R3AXB4R7A	Oxide Metal Film 4.7 1W ±5%
R73,74	R3DXBJ100A	Oxide Metal Film 10 2W ±5%
R75,76	R2EDZJ103APA	Carbon 10k 1/4W ±5%
R77	R2EDZJ472APA	Carbon 4.7k 1/4W ±5%
R78	R2EDZJ154APA	Carbon 150k 1/4W ±5%
R79	R2EDZJ681APA	Carbon 680 1/4W ±5%
R80	R2EDZJ122APA	Carbon 1.2k 1/4W ±5%
R81,82	R2EDUJ823A	Carbon 82k 1/4W ±5%
83,84		

### POWER SUPPLY P.C.B. Assy 131 0 4001 05652

Ref. No.	Parts Number	Description
△	4 2312 01400	Switch Push Power
	4 2312 04700	Switch Slide 4-2
△	4 2349 20240	Fuse T 1.6 A
△	4 2349 20310	Fuse T 500 mA
	131 2 6201 21500	Plate Heat Sink

<b>CAPACITORS</b>		
C01 △	4 2232 00550	Oil 0.01 μF 450V
C02	C1VRE-107A	Electrolytic 100 μF 35V
C03 △	4 2232 00430	Ceramic 0.01 μF x2 250V
C04	C1HRF-337A	Electrolytic 330 μF 50V
C05	C1HRY-476APA	Electrolytic 47 μF 50V
C06	C1HYDZ473A	Ceramic 0.047 μF 50V +80,-20%
C07	C1VRE-227A	Electrolytic 220 μF 35V
C08	C1HRE-227A	Electrolytic 220 μF 50V
C09	C1ERE-227A	Electrolytic 220 μF 25V
C10	C1HFKYK102APA	Mylar 0.001 μF 50V ±10%
C11	4 2232 00430	Ceramic 0.01 μF x2 250V
C12	C1ERE-228A	Electrolytic 2200 μF 25V
C13	C1ERE-227A	Electrolytic 220 μF 25V
C14	C1HYDZ473A	Ceramic 0.047 μF 50V +80,-20%
C15	C1CRE-227A	Electrolytic 220 μF 16V
C16	C1ERE-477A	Electrolytic 470 μF 25V
C17	4 2232 00430	Ceramic 0.01 μF x2 250V
C18	C1ERE-227A	Electrolytic 220 μF 25V
C19	C1CRE-227A	Electrolytic 220 μF 16V
C20	C0JRY-107APA	Electrolytic 100 μF 6.3V
C21	4 2232 00430	Ceramic 0.01 μF x2 250V

Ref. No.	Parts Number	Description
<b>CAPACITORS</b>		
C22	C1CRE-228A	Electrolytic 2200 μF 16V
C23	C1CRE-477A	Electrolytic 470 μF 16V
C24	C1CRY-107APA	Electrolytic 100 μF 16V
C26	C1ARY-227APA	Electrolytic 220 μF 10V
C27,28	C1HRE-107A	Electrolytic 100 μF 50V
C29,30	C1VRE-227A	Electrolytic 220 μF 35V
C31,32	C1ERY-107APA	Electrolytic 100 μF 25V

<b>SEMICONDUCTORS</b>		
D01,02	202 5 2470 13540	Diode, DS-135
D03	DNN-RD5R6EB2	Diode, RD5.6EB2
D04	202 5 3210 20020	Diode, GZA20U
D05	DNN-RD4R3EB1	Diode, RD4.3EB1
D06	202 5 2300 017101	Diode, DS-17
D07	202 5 2300 018101	Diode, DS-18
D08	202 5 3210 05610	Diode, GZA5.6L
D09,10	202 5 3210 24010	Diode, GZA24L
D11	202 5 2320 131101	Diode, DS131
D12	202 5 3210 06220	Diode, GZA6.2U
D13,14	205 5 9040 44210	Diode, DS-442
IC01	ITT-TA78L024AP	IC, TA78L024AP
IC02	IAA-FS-7812M	IC, FS-7812M
Q01,02	203 5 6830 43850	TR 2SD438 E, F
03		
Q04	203 5 6840 56050	TR 2SB560 E, F
Q05	203 5 5000 53660	TR 2SC536 F, G
Q06	TNN-2SD794--Q	TR 2SD794 Q, R

<b>RESISTORS</b>		
R01	R2EDPJ4R7A	Carbon 4.7 1/4W ±5%
R02	R2EDZJ102APA	Carbon 1k 1/4W ±5%
R03	R2EDZJ103APA	Carbon 10k 1/4W ±5%
R04	R2EDZJ221APA	Carbon 220 1/4W ±5%
R05	R2HXB4R391A	Oxide Metal Film 390 1/2W ±5%
R06	R2EDZJ272APA	Carbon 2.7k 1/4W ±5%
R07	R2HZPK2R2A	Fuse 2.2 1/2W ±10%
R08	R2EDZJ101APA	Carbon 100 1/4W ±5%
R09	R2HXB4R561A	Oxide Metal Film 560 1/2W ±5%
R10	R2EDPJ2R2A	Carbon 2.2 1/4W ±5%
R11	R2EDZJ101APA	Carbon 100 1/4W ±5%
R12	R2EDZJ102APA	Carbon 1k 1/4W ±5%
R13	R2EDZJ471APA	Carbon 470 1/4W ±5%
R14	R2HZPKR47A	Fuse 0.47 1/2W ±10%
R15	R2EDZJ561APA	Carbon 560 1/4W ±5%
R16	R2EDZJ102APA	Carbon 1k 1/4W ±5%
R17,18	R2HZPK471A	Fuse 470 1/2W ±10%
R19,20	R2EDZJ102APA	Carbon 1k 1/4W ±5%
21,22		

### L.E.D. DRIVE P.C.B. Assy 131 0 4001 05661

Ref. No.	Parts Number	Description
VR01,02	4 2222 01400	VR 10k-B
VR03,04	4 2222 00990	VR 1k-B

# PARTS LIST (Continued)

PHONO EQ P.C.B. Assy  
131 0 4001 05700

Ref. No.	Parts Number	Description
<b>CAPACITORS</b>		
C01,02 03,04	C1HRY-106APA	Electrolytic 10 $\mu$ F 50V
C05,06	C1HRY-105APA	Electrolytic 1 $\mu$ F 50V
C07,08	C1ERY-475APA	Electrolytic 4.7 $\mu$ F 25V

## SEMICONDUCTORS

D01,02 03,04	205 5 9040 44210	Diode, DS-442
IC01,02	206 5 2441 40910	IC, LB1409
Q01,02	203 5 6850 40050	TR 2SD400 E, F
Q03	203 5 7252 27450	TR 2SC2274 E, F

## RESISTORS

R01,02	R3DXBJ391A	Oxide Metal Film	390	2W	$\pm 5\%$
R03,04	R3AXB121A	Oxide Metal Film	120	1W	$\pm 5\%$
R05,06	R2EDZJ103APA	Carbon	10k	1/4W	$\pm 5\%$
R07,08	R2EDZJ102APA	Carbon	1k	1/4W	$\pm 5\%$
R09,10	R2EDZJ101APA	Carbon	100	1/4W	$\pm 5\%$
R11,12 13,14	R2EDZJ223APA	Carbon	22k	1/4W	$\pm 5\%$
R15,16	R2EDZJ103APA	Carbon	10k	1/4W	$\pm 5\%$
R17,18	R2EDZJ823APA	Carbon	82k	1/4W	$\pm 5\%$
R19,20	R2EDZJ183APA	Carbon	18k	1/4W	$\pm 5\%$
R21,22	R3DXBJ330A	Oxide Metal Film	33	2W	$\pm 5\%$
R23,24 25,26 27	R2HXB121A	Oxide Metal Film	120	1/2W	$\pm 5\%$
R28	R2EDZJ102APA	Carbon	1k	1/4W	$\pm 5\%$

## HEADPHONE JACK P.C.B. Assy 131 0 4001 05671

Ref. No.	Parts Number	Description
	4 2352 00800	Headphone Jack 3P

## SP TERMINAL 1 P.C.B. Assy 131 0 4001 05681

Ref. No.	Parts Number	Description
	4 2372 00090	SP Terminal 4P

## SP TERMINAL 2 P.C.B. Assy 131 0 4001 05691

Ref. No.	Parts Number	Description
	4 2372 00090	SP Terminal 4P

Ref. No.	Parts Number	Description
	4 2222 01860	VR 150k-Ax2, 250k-MN
	4 2312 04660	Switch Push 1Key
	4 2312 04690	Switch Push 8Key
	4 2352 00780	DIN Socket 5P
	4 2359 23180	Socket 4P
	4 2359 23220	RCA 6P Jack
	4 2369 22750	Plug 7P

## CAPACITORS

C01,02	C1HFK103APA	Mylar	0.01 $\mu$ F	50V	$\pm 10\%$
C03	C0JRY-227APA	Electrolytic	220 $\mu$ F	6.3V	
C04,05	C0JRY-227AP	Electrolytic	220 $\mu$ F	6.3V	
C06	C0JRY-227APA	Electrolytic	220 $\mu$ F	6.3V	
C07	C1ARY-476APA	Electrolytic	47 $\mu$ F	10V	
C08	C1ARY-476AP	Electrolytic	47 $\mu$ F	10V	
C09,10	C1ARY-476APA	Electrolytic	47 $\mu$ F	10V	
C11,12	C1ERY-475LPA	Electrolytic	4.7 $\mu$ F	25V	
C13,14	C0JRY-227AP	Electrolytic	220 $\mu$ F	6.3V	
C15,16	C0JRY-227APA	Electrolytic	220 $\mu$ F	6.3V	
C17,18	C1ARY-227APA	Electrolytic	220 $\mu$ F	10V	
C19,20	C1ARY-476APA	Electrolytic	47 $\mu$ F	10V	
C21,22	C1HRY-335LPA	Electrolytic	3.3 $\mu$ F	50V	
C23,24	C1HCZJ560SPA	Ceramic	56 pF	50V	$\pm 5\%$
C25,26	C0JRY-227APA	Electrolytic	220 $\mu$ F	6.3V	
C27,28	C1HCZJ101SPA	Ceramic	100 pF	50V	$\pm 5\%$
C29,30	C1HCZJ220SPA	Ceramic	22 pF	50V	$\pm 5\%$
C31,32	C1HFRJ183A	Mylar	0.018 $\mu$ F	50V	$\pm 5\%$
C33,34	C1HFRJ472A	Mylar	0.0047 $\mu$ F	50V	$\pm 5\%$
C35,36	C1HCZK331BPA	Ceramic	330 pF	50V	$\pm 10\%$
C37,38	C1HRY-475LPA	Electrolytic	4.7 $\mu$ F	50V	
C39,40	C1HCYK181APA	Ceramic	180 pF	50V	$\pm 10\%$
C41,42	C1HFK473APA	Mylar	0.047 $\mu$ F	50V	$\pm 10\%$
C43,44 45,46 47	C1ECZN103XPA	Ceramic	0.01 $\mu$ F	25V	$\pm 30\%$
C48,49	C1ERE-227A	Electrolytic	220 $\mu$ F	25V	

## SEMICONDUCTORS

D01,02	DNN-RD7R5EB2	Diode, RD7.5EB2
D03,04	205 5 9040 44210	Diode, DS-442
IC01,02	IKK-HA1457	IC, HA1457
Q01,02	TMM-2SC2385-F	TR 2SC2385 F, G, H
Q03,04	TMM-2SA978-F	TR 2SA978 F, G, H
Q05	203 5 6850 40050	TR 2SD400 E, F
Q06	203 5 6860 54450	TR 2SB544 E, F
Q07,08	INN-2SK104-J	TR 2SK104 J

## RESISTORS

R01,02	R2EDZJ8R2APA	Carbon	8.2	1/4W	$\pm 5\%$
R03,04	R2EDZJ681APA	Carbon	680	1/4W	$\pm 5\%$
R05,06 07,08 09,10	R2EDZJ182APA	Carbon	1.8k	1/4W	$\pm 5\%$
R11,12 13,14	R2EDZJ221APA	Carbon	220	1/4W	$\pm 5\%$
R15,16 17,18	R2EDZJ330APA	Carbon	33	1/4W	$\pm 5\%$
R19,20	R2EDZJ223APA	Carbon	22k	1/4W	$\pm 5\%$

## PARTS LIST (Continued)

Ref. No.	Parts Number	Description
<b>RESISTORS</b>		
R21,22 23,24	R2EDZJ101APA	Carbon 100 1/4W ±5%
R25,26	R2EDZJ104APA	Carbon 100k 1/4W ±5%
R27,28	R2EDZJ471APA	Carbon 470 1/4W ±5%
R29,30	R2EDZJ104APA	Carbon 100k 1/4W ±5%
R31,32	R2EDZJ331APA	Carbon 330 1/4W ±5%
R33,34	R2EDZJ184APA	Carbon 180k 1/4W ±5%
R35,36	R2EDZJ153APA	Carbon 15k 1/4W ±5%
R39,40	R2EDZJ471APA	Carbon 470 1/4W ±5%
R41,42	R2EDZJ473APA	Carbon 47k 1/4W ±5%
R43,44	R2EDZJ221APA	Carbon 220 1/4W ±5%
R45,46	R2EDZJ472APA	Carbon 4.7k 1/4W ±5%
R47,48	R2EDZJ822APA	Carbon 8.2k 1/4W ±5%
R49,50	R2EDZJ334APA	Carbon 330k 1/4W ±5%
R51,52	R2EDZJ222APA	Carbon 2.2k 1/4W ±5%
R53	R2EDZJ102APA	Carbon 1k 1/4W ±5%

### TONE AMP P.C.B. Assy 131 0 4001 05710

Ref. No.	Parts Number	Description
	4 2222 01341	VR 100k-Cx2
	4 2312 04670	Switch Push 2Key
	4 2312 04680	Switch Push 3Key

#### CAPACITORS

C01,02	C1HRY-335LPA	Electrolytic 3.3 μF 50V
C03,04	C1HCYK560APA	Ceramic 56 pF 50V ±10%
C05,06	C1HCYK270APA	Ceramic 27 pF 50V ±10%
C07,08	C1HCYD100APA	Ceramic 10 pF 50V ±0.5%
C09,10	C1HCYK101APA	Ceramic 100 pF 50V ±10%
C11,12	C1HRY-225APA	Electrolytic 2.2 μF 50V
C13,14	C1HRY-475LPA	Electrolytic 4.7 μF 50V
C15,16	C1ERY-475APA	Electrolytic 4.7 μF 25V
C17,18	C1HFKY333APA	Mylar 0.033 μF 50V ±10%
C19,20	C1HFRJ184ML	Mylar 0.18 μF 50V ±5%
C21,22	C1HFKY333APA	Mylar 0.033 μF 50V ±10%
C23,24	C1HFRJ184ML	Mylar 0.18 μF 50V ±5%
C25,26	C1HFKY222AP	Mylar 0.0022 μF 50V ±10%
C27,28	C1HFKY123APA	Mylar 0.012 μF 50V ±10%
C29,30	C1HFKY222APA	Mylar 0.0022 μF 50V ±10%
C31,32	C1HFKY103APA	Mylar 0.01 μF 50V ±10%
C33,34	C1HRY-475APA	Electrolytic 4.7 μF 50V
C35,36	C1HFKY223APA	Mylar 0.022 μF 50V ±10%
C37,38	C1HCYK181APA	Ceramic 180 pF 50V ±10%
C39,40 41,42	C1HFRJ184ML	Mylar 0.18 μF 50V ±5%
C43,44	C1HRY-225LPA	Electrolytic 2.2 μF 50V
C45,46	C1ERE-227A	Electrolytic 220 μF 25V
C47	C1HRY-474APA	Electrolytic 0.47 μF 50V

#### SEMICONDUCTORS

IC01,02	IKK-HA1457	IC, HA1457
---------	------------	------------

Ref. No.	Parts Number	Description
<b>RESISTORS</b>		
R01,02	R2EDZJ471APA	Carbon 470 1/4W ±5%
R03,04 05,06	R2EDZJ394APA	Carbon 390k 1/4W ±5%
R07,08	R2EDZJ104APA	Carbon 100k 1/4W ±5%
R09,10	R2EDZJ473APA	Carbon 47k 1/4W ±5%
R11,12 13,14	R2EDZJ471APA	Carbon 470 1/4W ±5%
R15,16	R2EDZJ123APA	Carbon 12k 1/4W ±5%
R17,18	R2EDZJ274APA	Carbon 270k 1/4W ±5%
R21,22	R2EDZJ222APA	Carbon 2.2k 1/4W ±5%
R25,26	R2EDZJ104APA	Carbon 100k 1/4W ±5%
R27,28	R2EDZJ222APA	Carbon 2.2k 1/4W ±5%
R29,30	R2EDZJ393APA	Carbon 39k 1/4W ±5%
R31,32	R2EDZJ105APA	Carbon 1M 1/4W ±5%
R33,34	R2EDZJ104APA	Carbon 100k 1/4W ±5%
R35,36	R2EDZJ221APA	Carbon 220 1/4W ±5%
R37	R2EDZJ102APA	Carbon 1k 1/4W ±5%

### L.E.D. LAMP P.C.B. Assy 131 0 4001 05720

Ref. No.	Parts Number	Description
	4 6122 01910	Lamp Assy

#### SEMICONDUCTORS

D01,02 03,04 05,06 07,08 09,10 11,12 13,14 15,16 17,18	DYY-SLR-54GG	Diode, SLR-54GG (LED)
D19,20	202 5 2470 13540	Diode, DS-135

#### RESISTORS

R01,02 03,04 05,06 07,08 09,10 11,12 13,14 15,16 17,18	R2EDZJ101APA	Carbon 100 1/4W ±5%
--	--------------	---------------------


### POWER INDICATOR P.C.B. Assy 131 0 4001 06611

Ref. No.	Parts Number	Description
<b>SEMICONDUCTORS</b>		
D01	DYY-SLR-54UR	Diode, SLR-54UR (LED)


#### RESISTORS

R01	R2EDZJ272APA	Carbon 2.7k 1/4W ±5%
-----	--------------	----------------------


# POINT TO POINT WIRING DIAGRAM (TOP VIEW)



# POINT TO POINT WIRING DIAGRAM (BOTTOM VIEW)



# SCHEMATIC DIAGRAM (RF CONTROL P.C.B.)




## NOTES:


1. All resistors values are indicated in "ohm" ( $K=10^3$ ,  $M=10^6$ ).
  2. All capacitors values are indicated in " $\mu F$ " ( $P=10^{-12}$ ).
  3. All voltages indicated on the schematics are measured under the following conditions.
    - a. Use a V.T.V.M.
    - b. All voltages  $\pm 10\%$  with respect to chassis ground
    - c. No signals at input terminals
    - d. AC input at 220 volts 50 Hz
  4. This is a basic schematic diagram.
- Because Fisher products are subject to continuous improvement, Fisher Corporation reserves the right to make any changes or modifications without notice.




SCHEMATIC DIAGRAM



**PRODUCT SAFETY NOTICE**

PRODUCT SAFETY SHOULD BE CONSIDERED WHEN A COMPONENT REPLACEMENT IS MADE IN ANY AREA OF A UNIT. COMPONENTS INDICATED BY A MARK  IN THIS SCHEMATIC DIAGRAM SHOW COMPONENTS WHOSE VALUE HAS SPECIAL SIGNIFICANCE TO PRODUCT SAFETY. IT IS PARTICULARLY RECOMMENDED THAT ONLY PARTS SPECIFIED ON THE ATTACHED PARTS LIST BE USED FOR COMPONENT REPLACEMENT POINTED OUT BY THE MARK.

## FRONT END SCHEMATIC DIAGRAM



# FISHER

Service/Ersatzteillager:  
FISHER HiFi Europa Vertriebs-GmbH  
Shönstraße 80, 8000 München 90  
Telefon 089/2379-7  
Telex 5-212384 D  
Wenden Sie sich bitte mit technischen  
Fragen an diese Adresse.

**Verwaltung, Verkauf und Auslieferungslager:**  
**FISHER HiFi Europa Vertriebs-GmbH**  
 Truderingstraße 13, 8000 München 80  
 Telefon 089/4145-0  
 Telex 5-24665 D  
 5-24033 D

PRINTED IN JAPAN  
'81/Oct. **WM-6632**